

## ELECTRIC TELESCOPIC BOOM LIFTS

# TB20EJ PLUS(TB660EJ PLUS)

Compliant with GB / CE / ANSI / EAC standards

## PRODUCT HIGHLIGHTS

### Green

- Comfortable working environment without noise pollution, meet indoor or emissions-critical site requirements

### Precision Performance

- Three full-scale joysticks for gradual proportional control, Operate with smooth starting and stopping and precision approach to your worksite target
- The Sinoboom IoT system and intelligent 7-inch screen can efficiently control the use and behavior of the equipment

### Economical

- Battery quality assurance, low failure rate and reduced maintenance costs compared with diesel power, which reduces overall operating cost

### Oscillating Axle Function

- Both the active and inactive states have an oscillating axle function, allowing work to be performed on inclines and uneven ground



#### Standard Features

Active oscillating axle	7-in display screen	4WD x 2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	4-wheel brake
Hydraulic platform leveling	160° Platform rotation	Weighing system
Tilt protection system	Max tilt rating to 5°	Emergency stop system
Flashing beacon	Horn & buzzer	Emergency lowering system
Footswitch	Manual storage box	Fault diagnosis system
Foam-filled non-marking tires	2.44m(8') platform with swinging gate	Secondary guarding device
Telematics-ready connector		

#### Options & Accessories

AC power to the platform	Solid tires	1.45m (4'9") platform
1.83m(6') work platform	Half mesh (for platform with swinging gate)	Platform work light
Range Extender	Lithium battery	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

[SINOBOOM.COM](http://SINOBOOM.COM) | [SALES@SINOBOOM.COM](mailto:SALES@SINOBOOM.COM)

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

**ELECTRIC TELESCOPIC BOOM LIFTS**

**TB20EJ PLUS(TB660EJ PLUS)**

Compliant with GB / CE / ANSI / EAC standards

Model	TB20EJ PLUS(TB660EJ PLUS)
<b>Dimensions</b>	
Max Platform Height	20 m (65'7")
Max Working Height	22 m (72'2")
Max Horizontal Reach(Restricted/Restricted/Unrestricted)	13.85 m/15.4 m/16.7m (45'5"/50'6"/54'9")
A Stowed Length	9.99 m (32'9")
B Stowed Width	2.49 m (8'2")
C Stowed Height	2.79 m (9'2")
Stowed Length (Transport)	8.12 m (26'8")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	2.77 m (9' 1")
D Wheelbase	2.49 m (8' 2")
Ground Clearance	0.39 m (1' 3")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
<b>Performance</b>	
Max Platform Capacity (Restricted/Restricted/Unrestricted)	454 kg/300 kg/250 kg (1,000 lbs/661 lbs/551 lbs)
Max Platform Occupants (Restricted/Restricted/Unrestricted)	3 Persons/2 Persons/2 Persons
Drive Speed (Stowed / Raised)	0 ~ 4.8 km/h (0 ~ 3 mph)   0 ~ 1.1 km/h (0 ~ 0.68 mph)
Gradeability	35%
Turntable Rotation	360° /Continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	2.4 m/5.55 m (7'10"/18'3")
Turntable Tail-Swing	1.45 m (4'9")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	355/55D625 (foam-filled)   36×14-20 (solid)
<b>Power</b>	
Drive × Steer	4WD×2WS
Batteries	48 V, 480 Ah (lead acid battery) 51.2 V, 500 Ah (lithium battery)
Hydraulic Tank Capacity	180 L (39.6 gal (UK)/47.6 gal (US))
System Voltage	48 VDC
<b>Weight</b>	
Weight	11,950 kg (26,345 lbs)
Standards Compliance	GB/CE/ANSI/EAC

